
quaerere-base-flask Documentation

Release 0.3.1.dev2

Caitlyn O'Hanna

Sep 21, 2019

Contents:

1	API	1
2	About	5
2.1	Links	5
3	Installation	7
4	Usage	9
5	Indices and tables	11
	Python Module Index	13
	Index	15


```
class quaerere_base_flask.schemas.ArangoDBFilterSchema (extra=None,    only=None,
                                                         exclude=(),        pre-
                                                         fix="",            strict=None,
                                                         many=False,       con-
                                                         text=None,        load_only=(),
                                                         dump_only=(),     par-
                                                         tial=False)
```

:py:attr: filters [:py:class: ~.fields.List] condition

:py:attr: variables [:py:class: ~.fields.Dict] variables used to bind

```
class quaerere_base_flask.schemas.ArangoDBMetadataSchema (extra=None, only=None,
                                                            exclude=(),        pre-
                                                            fix="",            strict=None,
                                                            many=False,       con-
                                                            text=None,        load_only=(),
                                                            dump_only=(),     par-
                                                            tial=False)
```

Schema for ArangoDB insert/update metadata

:py:attr: _id [:py:class: *marshmallow.fields.String*][required=True] Id of document

:py:attr: _key [:py:class: ~*marshmallow.fields.String*][required=True] Key of document

:py:attr: _rev [:py:class: ~.fields.String][required=True] Current revision of document

:py:attr: _old_rev [:py:class: ~.fields.String] Previous revision of document

```
class quaerere_base_flask.views.BaseView
```

Base class for defining a Restful access method to a resource

BaseView provides basic Restful access to a resource defined by a given data object and schema.

Current supported functionality

- *index()*
- *get()*

- `post()`
- `put()`
- `patch()`
- `delete()`
- `find()`

Supported callbacks

- pre and post create (HTTP POST)
- pre and post read (HTTP GET)
- pre and post update (HTTP PUT and PATCH)
- pre and post delete (HTTP DELETE)

`__init__()`

`_post_create_callback(resp_data)`

Call back function ran *after* object is created in data store

Parameters `resp_data` – Response data

Returns

`_post_delete_callback(key, resp_data)`

Call back function ran *before* object is deleted in data store

Parameters

- `key` – Object key
- `resp_data` – Response data

Returns

`_post_read_callback(key, resp_data)`

Call back function ran *after* object is read from data store

Parameters

- `key` – Object key
- `resp_data` – Response data

Returns

`_post_update_callback(key, resp_data, http_method)`

Call back function ran *after* object is updated in data store

Parameters

- `key` – Object key
- `resp_data` – Response data
- `http_method` – ‘patch’ or ‘put’

Returns

`_pre_create_callback(req_data)`

Call back function ran *before* object is created in data store

Parameters `req_data` – Request data

Returns

`_pre_delete_callback` (*key*)

Call back function ran *before* object is deleted in data store

Parameters **key** – Object key

Returns

`_pre_read_callback` (*key*)

Call back function ran *before* object is read from data store

Parameters **key** – Object key

Returns

`_pre_update_callback` (*key, req_data, http_method*)

Call back function ran *before* object is updated in data store

Parameters

- **key** – Object key
- **req_data** – Request data
- **http_method** – ‘patch’ or ‘put’

Returns

`delete` (*key*)

Delete an object

Parameters **key** – Key of object

Returns DB Delete metadata

`find` ()

Find an object based on criteria

Returns objects

`get` (*key*)

Get a specific object by key

Parameters **key** – Primary key of an object to retrieve

Returns Object of provided key

`index` ()

Returns all objects

Returns All objects of the model type

`patch` (*key*)

Update specific data elements

Parameters **key** – Key of object

Returns DB Update metadata

`post` ()

Create a new object

Returns DB Insert metadata

`put` (*key*)

Update all fields on an object

Parameters **key** – Key of object

Returns DB Update metadata

`quaerere_base_flask.views.register_views(app, view_module, version, prefix='api')`

Registers FlaskView classes to the Flask app passed as argument

Parameters

- **app** (*flask.Flask*) – Flask app instance
- **version** (*str*) – API version string
- **prefix** (*str* or *None*) – String to prepend to API path

Returns

quaerere-base-flask contains the common elements shared between components of the Quaerere Platform.

2.1 Links

- Documentation: <http://quaerere-base-flask.readthedocs.io/>
- PyPI: <https://pypi.org/project/quaerere-base-flask/>
- Source: <https://github.com/QuaererePlatform/quaerere-base-flask.git>

CHAPTER 3

Installation

Using pip:

```
pip install quaerere-base-flask
```

Or using setup.py:

```
python setup.py install
```

Tests can be ran using:

```
python setup.py test
```

Documentation can be generated using:

```
python setup.py build_sphinx
```


CHAPTER 4

Usage

CHAPTER 5

Indices and tables

- `genindex`
- `modindex`
- `search`

q

- `quaerere_base_flask`, [1](#)
- `quaerere_base_flask.schemas`, [1](#)
- `quaerere_base_flask.views`, [1](#)

Symbols

`__init__()` (*quaerere_base_flask.views.BaseView method*), 2
`_post_create_callback()` (*quaerere_base_flask.views.BaseView method*), 2
`_post_delete_callback()` (*quaerere_base_flask.views.BaseView method*), 2
`_post_read_callback()` (*quaerere_base_flask.views.BaseView method*), 2
`_post_update_callback()` (*quaerere_base_flask.views.BaseView method*), 2
`_pre_create_callback()` (*quaerere_base_flask.views.BaseView method*), 2
`_pre_delete_callback()` (*quaerere_base_flask.views.BaseView method*), 2
`_pre_read_callback()` (*quaerere_base_flask.views.BaseView method*), 3
`_pre_update_callback()` (*quaerere_base_flask.views.BaseView method*), 3

A

ArangoDBFilterSchema (class in *quaerere_base_flask.schemas*), 1
ArangoDBMetadataSchema (class in *quaerere_base_flask.schemas*), 1

B

BaseView (class in *quaerere_base_flask.views*), 1

D

`delete()` (*quaerere_base_flask.views.BaseView method*), 3

F

`find()` (*quaerere_base_flask.views.BaseView method*), 3

G

`get()` (*quaerere_base_flask.views.BaseView method*), 3

I

`index()` (*quaerere_base_flask.views.BaseView method*), 3

P

`patch()` (*quaerere_base_flask.views.BaseView method*), 3
`post()` (*quaerere_base_flask.views.BaseView method*), 3
`put()` (*quaerere_base_flask.views.BaseView method*), 3

Q

quaerere_base_flask (module), 1
quaerere_base_flask.schemas (module), 1
quaerere_base_flask.views (module), 1

R

`register_views()` (in *quaerere_base_flask.views*), 4